



Category 3 high density voice patch panels offer a cost effective method for integrating voice circuits into standard structured cabling systems. Available in both 25 and 50 ports on a 1U 19" footprint, ideal for maximising rack space.

Features

- 19" rack mountable
- Accepts 24-26 AWG
- Supplied with fixings and earthing wire
- IDC punch down
- 25 or 50 RJ45 ports on 1U footprint
- Integral cable management and grounding clamps

Applications

Voice integration into standard structured cabling systems

Specification

MECHANICAL	VALUE
Housing Material	PBT + 15% GF UL94V-0
Panel Frame	Carbon Steel, Powder Coating
Contact Material	PC UL94V-0 Contact: Phosphor Bronze + Nickel Plating
RJ45 Jack Life	Min 750 Insertions
IDC Life	Min 200 Terminations

Standards Compliance

- Category 3
- ISO/IEC 11801 : 2002
- ANSI/EIA/TIA 568B.2.1 : 2002
- UL approved

Ordering Information

DESCRIPTION

Optronics Category 3 1U 25 port voice patch panel Black - UL approved
Optronics Category 3 1U 50 port voice patch panel Black - UL approved

PART NO.

CAT3+LSA25
CAT3+LSA50



Further Information

- For additional information please contact your sales representative
- Downloaded from <http://www.fibrefab.com/products/copper-structured-cabling/cat-3/cat-3-voice-patch-panel/>
- FibreFab reserves the right to make changes to the product specifications in this datasheet at any time without notice
- Information in this document is correct as of May 13, 2014

Europe

- +44 870 127 3330
- sales@fibrefab.com

Americas

- +1 410 242 9026
- sales@fiberfabinc.com

Middle East & Africa

- +971 4 443 0168
- me@optronicsnet.com

Asia Pacific

- +86 755 2561 3694
- asia@fibrefab.com